

AERO TAPE TRUE Indoor · Static White

Features

- High CRI 95+ SMD tape with true-to-life color accuracy
- IP20 rated, ideal for indoor uses
- 5 years warranty

Applications

Under cabinets, coves, shelves, backlighting, bedrooms, stairs, etc.



Dimensions



Order Code (For LED tape)

Series	Environment	Voltage	Temp./Color	Power
AEROT	D2-Dry (IP20)	24-DC24V	27-2700K	152-1.52W/ft
			30-3000K	305-3.05W/ft
			40-4000K	457-4.57W/ft
			65-6500K	

Assembly Builder

Left Feed Entry			
F	Front	OW	Open wire 3.28ft (1m), 20 AWG
C	Closed	MC	Male connector with 0.66ft (20cm) cable, 20 AWG
		FC	Female connector with 0.66ft (20cm) cable, 20 AWG
		NA	Only for Closed Feed Entry

Assembly Builder

Right Feed Entry			Illuminated Length ¹
F	Front	OW	Open wire 3.28ft (1m), 20 AWG
C	Closed	MC	Male connector with 0.66ft (20cm) cable, 20 AWG
		FC	Female connector with 0.66ft (20cm) cable, 20 AWG
		NA	Only for Closed Feed Entry

Channel Order Code

Product Code ¹	Colors	Lens	Lengths
Please select on the Channel Compatibility page	S = Silver anodized	OP - Opal	3.28ft (1m)
	W = White lacquered	FR - Frosted	6.56ft (2m)
	B = Black anodized	CL - Clear	

¹. Production length = Illuminated length + End cap extension length (refer to below page for extension length of each end cap).

¹. Including 3.28ft/6.56ft lens cover + 2pcs end caps+2pcs mounting clips.

Temp./Color	1.52W/ft	3.05W/ft	4.57W/ft
2700K	134	259	363
3000K	136	268	375
4000K	144	279	391
6500K	141	273	383
Max. Run for Class 2	50.5ft (15.4m)	25.2ft (7.7m)	16.8ft (5.1m)
Max. Run Supported Length	29.5ft (9m)	23ft (7m)	19.7ft (6m)


*Typically installations in USA and Canada comply with Class 2 requirements.

Technical Details	
Width	0.39in. (10mm)
LED Quantity	36 LEDs/ft (120 LEDs/M)
Beam Angle	120°
Efficacy	91.5lm/W @4000K 3.05W
CRI	Ra ≥ 95
LED MacAdam	2 steps
Average Life (L70)	> 54,000 hours
Max. Length Per Reel	164ft (50m)
Storage Temperature	-13-140°F (-25°C~ 60°C)
Ambient Temperature	-4-113°F (-20°C~ 45°C)

Feed Entry Options



Connector Wire Options



AERO TAPE TRUE Indoor · Static White

Channel Compatibility

Lens Type & Light Transmission

* Non-standard option, please contact us for customization support.

CL Clear

FR Frosted

OP Opal

Surface			
BEI201 CL 61% FR 56% OP 46%	BEI202 CL 62% FR 57% OP 47%	BEI205 CL 82% FR 75% OP 61%	BEI215 CL 55% FR 50% OP 41%
BEI302 CL 84% FR 76% OP 62%	BEI303 CL 64% FR 59% OP 48%	BEI415 CL 57% FR 52% OP 42%	BEI815 CL 51% FR 47% OP 38%
BEI919 CL 76% FR 69% OP 57%	BE2020 CL 77% FR 71% OP 58%		
Mud-In			
BE5615 CL 58% FR 53% OP 44%	BE7615 CL 71% FR 65% OP 53%		

AERO TAPE TRUE Indoor · Static White

Recessed			
BE1204 CL 83% FR 75% OP 62%	BE1207 CL 61% FR 55% OP 45%	BE2015 CL 56% FR 51% OP 42%	BE5035 CL 55% FR 50% OP 41%
BE6575 CL 64% FR 58% OP 48%			

Corner			
BE1001 CL 88% FR 80% OP 66%	BE1002 CL 84% FR 77% OP 63%	BE1101 CL 60% FR 55% OP 45%	BE1203 CL 74% FR 67% OP 55%

Suspended			
BE3535 CL 56% FR 51% OP 42%	BE5075 CL 63% FR 58% OP 47%	BE60 CL 87% FR 79% OP 65%	

AERO TAPE TRUE Indoor · Static White

Specialty			
BE1806 Bendable surface mounted CL 89% FR 81% OP 66% 	BE2009 Coves CL 57% FR 52% OP 42% 	BE3511 Borderless Bi-Color Panel CL 68% FR 62% OP 51% 	BE4615 Borderless Inside Corner CL 59% FR 54% OP 44%
BE5315 Borderless Outside Corner CL 59% FR 54% OP 44% 	BE6728 Staircase CL 55% FR 50% OP 41% 	BE7030 Cove Recessed Borderless OP 63% 	BE8833 Cove Recessed / Double-Layer Borderless CL 58% FR 53% OP 43%

Connectors & Additional Accessories (Optional, purchase for extra)

N6012-STCN-2P-10 Strip to cable connector without wire, for 0.39in. (10mm) tape, 2 pin	N6012-STC-2P-10 Strip to cable connector with 5.9lin. (15cm) wire, for 0.39in. (10mm) tape, 2 pin	N6012-STSJ-2P-10 Strip to strip jumper connector with 5.9lin. (15cm) wire, for 0.39in. (10mm) tape, 2 pin	N6012-STDCB-2P-10 Strip to cable with black male & female connector, for 0.39in. (10mm) tape, 2 pin	N6012-STDCW-2P-10 Strip to cable with white male & female connector, for 0.39in. (10mm) tape, 2 pin
N6012-STS-2P-10 Strip to strip connector, for 0.39in. (10mm) tape, 2 pin	C6012-LC-2P-10 L-shaped corner connector, for 0.39in. (10mm) tape, 2 pin	C6012-RC-2P-10 R-shaped corner connector, for 0.39in. (10mm) tape, 2 pin	MCB-DC-44 Male DC connector with 0.66ft (20cm) cable, IP44, Dry & damp, 20 AWG	FCB-DC-44 Female DC connector with 0.66ft (20cm) cable, IP44, Dry & damp, 20 AWG
VHB VHB 3M adhesive back tape, stronger stickiness				

AERO TAPE TRUE Indoor · Static White

Drivers

Non-dimmable							
Code	Max Load	Input	Output	Class 2	With Junction Box	Environment	Size (L x W x H)
KV-24030-ASW	30W	100-277VAC	24V	Yes	No	Dry/Damp	6.1 x 2.1 x 0.8in. (15.5 x 5.3 x 2cm)
KV-24060-ASW	60W						7 x 2.4 x 0.9in. (17.8 x 6.1 x 2.3cm)
KV-24096-ASW	96W					Dry/Damp/Wet	9.1 x 2.8 x 1.7in. (23.1 x 7.1 x 4.3cm)
KV-24150-ASW	150W			10.1 x 3.1 x 1.9in. (25.7 x 7.9 x 4.8cm)			
KV-24200-ASW	200W			No			10.1 x 3.1 x 1.9in. (25.7 x 7.9 x 4.8cm)
KV-24300-ASW	300W						10.9 x 3.1 x 1.9in. (27.7 x 7.9 x 4.8cm)

Phase cut/Triac-dimmable							
Code	Max Load	Input	Output	Class 2	With Junction Box	Environment	Size (L x W x H)
KVF-24030-TDW	30W	100-277VAC	24V	Yes	No	Dry/Damp	6.1 x 2.1 x 0.8in. (15.5 x 5.3 x 2cm)
KVF-24060-TDW	60W						7 x 2.4 x 0.9in. (17.8 x 6.1 x 2.3cm)
KVF-24096-TDW	96W					Dry/Damp/Wet	9.1 x 2.8 x 1.7in. (23.1 x 7.1 x 4.3cm)
KVF-24150-TDW	150W						10.1 x 3.1 x 1.9in. (25.7 x 7.9 x 4.8cm)
KVF-24200-TDW	200W						10.1 x 3.1 x 1.9in. (25.7 x 7.9 x 4.8cm)
KVF-24300-TDW	300W						10.9 x 3.1 x 1.9in. (27.7 x 7.9 x 4.8cm)


4 in 1-dimmable (0-10V/1-10V/Potentiometer/10V PWM)							
Code	Max Load	Input	Output	Class 2	With Junction Box	Environment	Size (L x W x H)
KVD-24030-DIM	30W	100-277VAC	24V	Yes	No	Dry/Damp	6.1 x 2.1 x 0.8in. (15.5 x 5.3 x 2cm)
KVD-24060-DIM	60W						7 x 2.4 x 0.9in. (17.8 x 6.1 x 2.3cm)
KVD-24096-DIM	96W					Dry/Damp/Wet	9.1 x 2.8 x 1.7in. (23.1 x 7.1 x 4.3cm)
KVD-24150-DIM	150W			No			10.1 x 3.1 x 1.9in. (25.7 x 7.9 x 4.8cm)
KVD-24200-DIM	200W						13.4 x 1.1 x 7.3in. (34 x 27.9 x 18.5cm)
KVD-24300-DIM	300W	100-277VAC	24V	No	No	Dry/Damp/Wet	8.7 x 3.7 x 1.6in. (22 x 9.3 x 4.1cm)

5 in 1-dimmable (Triac/0-10V/1-10V/Potentiometer/10V PWM)							
Code	Max Load	Input	Output	Class 2	With Junction Box	Environment	Size (L x W x H)
KVG-24030-DW	30W	100-277VAC	24V	Yes	No	Dry/Damp	6.1 x 2.1 x 0.8in. (15.5 x 5.3 x 2cm)
KVG-24060-DW	60W						7 x 2.4 x 0.9in. (17.8 x 6.1 x 2.3cm)
KVG-24096-DW	96W					Dry/Damp/Wet	9.1 x 2.8 x 1.7in. (23.1 x 7.1 x 4.3cm)
KVG-24150-DW	150W			10.1 x 3.1 x 1.9in.(25.7 x 7.9 x 4.8cm)			
KVG-24200-DW	200W			No			13.4 x 11 x 7.3in.(34 x 27.9 x 18.5cm)
KVG-24300-DW	300W						10.9 x 3.1 x 1.9in.(27.7 x 7.9 x 4.8cm)


AERO TAPE TRUE Indoor · Static White

Wiring Diagram

Non-dimmable



Phase cut/Triac-dimmable



4 in 1-dimmable (0-10V/1-10V/Potentiometer/10V PWM)



5 in 1-dimmable (Triac/0-10V/1-10V/Potentiometer/10V PWM)



AERO TAPE TRUE Indoor · Static White

24V Voltage Drop & Maximum Wire Length Chart

Based on 24V voltage with a 3% voltage drop allowance. Indicates the maximum wire length from the power supply to the start of the run.

Total Load	10 AWG	12 AWG	14 AWG	16 AWG	18 AWG	20 AWG	22 AWG	24 AWG
5W / 0.2A	1730 ft (527.3 m)	1090 ft (332.2 m)	680 ft (207.3 m)	430 ft (131.1 m)	270 ft (82.3 m)	170 ft (51.8 m)	107 ft (32.6 m)	68 ft (20.7 m)
10W / 0.4A	784 ft (239.0 m)	539 ft (164.3 m)	345 ft (105.2 m)	215 ft (65.5 m)	134 ft (40.8 m)	85 ft (25.9 m)	52 ft (15.8 m)	34 ft (10.4 m)
15W / 0.6A	576 ft (175.6 m)	363 ft (110.6 m)	228 ft (69.5 m)	144 ft (43.9 m)	91 ft (27.7 m)	57 ft (17.4 m)	36 ft (11.0 m)	23 ft (7.0 m)
20W / 0.8A	397 ft (121.0 m)	272 ft (82.9 m)	174 ft (53.0 m)	109 ft (33.2 m)	68 ft (20.7 m)	43 ft (13.1 m)	27 ft (8.2 m)	17 ft (5.2 m)
25W / 1.0A	346 ft (105.5 m)	218 ft (66.4 m)	137 ft (41.8 m)	86 ft (26.2 m)	55 ft (16.8 m)	34 ft (10.4 m)	22 ft (6.7 m)	14 ft (4.3 m)
30W / 1.2A	263 ft (80.2 m)	181 ft (55.2 m)	115 ft (35.1 m)	72 ft (21.9 m)	45 ft (13.7 m)	27 ft (8.2 m)	17 ft (5.2 m)	12 ft (3.7 m)
35W / 1.5A	247 ft (75.3 m)	156 ft (47.5 m)	98 ft (29.9 m)	62 ft (18.9 m)	39 ft (11.9 m)	25 ft (7.6 m)	16 ft (4.9 m)	10 ft (3.0 m)
40W / 1.7A	197 ft (60.0 m)	135 ft (41.1 m)	86 ft (26.2 m)	54 ft (16.5 m)	33 ft (10.1 m)	21 ft (6.4 m)	13 ft (4.0 m)	9 ft (2.7 m)
45W / 1.9A	192 ft (58.5 m)	121 ft (36.9 m)	76 ft (23.2 m)	48 ft (14.6 m)	31 ft (9.4 m)	19 ft (5.8 m)	12 ft (3.7 m)	8 ft (2.4 m)
50W / 2.1A	158 ft (48.2 m)	108 ft (32.9 m)	69 ft (21.0 m)	43 ft (13.1 m)	27 ft (8.2 m)	17 ft (5.2 m)	10.5 ft (3.2 m)	7 ft (2.1 m)
60W / 2.5A	131 ft (39.9 m)	90 ft (27.4 m)	57 ft (17.4 m)	36 ft (11.0 m)	22 ft (6.7 m)	14 ft (4.3 m)	9 ft (2.7 m)	6 ft (1.8 m)
70W / 2.9A	112 ft (34.1 m)	77 ft (23.5 m)	49 ft (14.9 m)	31 ft (9.4 m)	19 ft (5.8 m)	12 ft (3.7 m)	7.5 ft (2.3 m)	5 ft (1.5 m)
80W / 3.3A	98 ft (29.9 m)	68 ft (20.7 m)	43 ft (13.1 m)	27 ft (8.2 m)	17 ft (5.2 m)	11 ft (3.4 m)	6.8 ft (2.1 m)	5 ft (1.5 m)
90W / 3.8A	97 ft (29.6 m)	61 ft (18.6 m)	39 ft (11.9 m)	24 ft (7.3 m)	15 ft (4.6 m)	9 ft (2.7 m)	6 ft (1.8 m)	4 ft (1.2 m)
100W / 4.2A	82 ft (25.0 m)	56 ft (17.1 m)	36 ft (11.0 m)	22 ft (6.7 m)	14 ft (4.3 m)	8 ft (2.4 m)	5.3 ft (1.6 m)	4 ft (1.2 m)